


SENZER®

Super power

Lithium Battery Series

LFP12020(12V20AH)



SENZER Lithium Series Batteries provide superior performance, capacities and reliability. Using state of high power cell technology the lithium series is designed for environmentally sensitive areas that require enhanced cycle life capabilities in commercial, industrial, residential, and private applications. The maintenance free construction and advanced design features makes the lithium Series the definitive choice for a wide variety of markets; Solar and Renewable Energy Storage; Electric Vehicle and Golf cart; Industrial equipment, Floor Machines, Forklifts, Aerial lifts, and Robotics; Marine, RV, and no-idle solutions; Mobility and Medical Equipment; Telecom, Broadband and Cable TV; UPS systems.

Applications



ELECTRICAL SPECIFICATIONS

Nominal Voltage	12.8	V
Amp Hour Capacity	20	AH
Reserve Capacity @ 10A	120	min
Energy Density	256	Wh
Resistance - Milliohms	< 80	
Efficiency - round trip	> 99.5%	
Self Discharge per Month	< 3%	
Max 4 - series connections	12-48V	
Parallel connections	No Limited	

DISCHARGE SPECIFICATIONS

Max Cont Discharge current	20	A
Peak Discharge Current 3C	60	A
BMS Current Cut Off	>20.5A	10S
BMS Current Cut Off	>30A	3S
BMS Current Cut Off	>60A	1S
BMS Voltage Cut Off	10V	
BMS Reconnect Voltage	12V	

TEMPERATURE SPECIFICATIONS

Discharge Temperature	(-20 to 60C)
Charge Temperature	(-20 to 45C)
Storage Temperature	(-5 to 35C)
BMS High Temp Cut Off	80C
BMS Reconnect Temp	50C
IP	50

MECHANICAL SPECIFICATIONS

Dimensions	181X77X167mm
Weight	2 KGS
Terminal Type	M5
Terminal Torque	6.2NM
Case Material	ABS
Case IP Rating	IP56
Cell Type - Chemistry	LiFePO4
Cell Type	Prismatic


CHARGE SPECIFICATIONS

Recommend Charge current	0.05C-0.5C
Max Charge current	1C
Charge current (0 to -10C)	<0.1C
Charge current (-20 to -10C)	<0.05C
Recommend Charge current voltage	14.2 - 14.6V
BMS Charge voltage cut off	15.0V
BMS Reconnect voltage	14.4V
Balancing voltage	14


Safety and Performance Specifications

Certifications	CB / CE UN38.3 UL1642 @ cell UN3480, CLASS 9
Shipping Classification	

Different DOD Discharge Cycle Life Curve 1C 25C



Different Temperature Discharge Curve(0.2C)



State of Charge Curve(0.5C, 25°C)

